

# Simple, Powerful and Optimised for video



## SE422 EnterpriseServer

### **Features**

#### PREDICTABLE PERFORMANCE

A powerful appliance with a finely-tuned OS, designed for video processing and recording. Award-winning technologies include VSOP Video Stream Optimisation delivering smooth video recording and playback. This eliminates disk fragmentation and the resulting frame loss for continuous write performance.

#### **OPEN PLATFORM**

All major OS and Video Management Software can be easily integrated and pre-loaded, having been pre-tested and qualified.

#### **CHOOSE YOUR SOFTWARE**

Your preferred video analytics software can be pre-loaded and ready to run at installation. These include facial recognition, abnormal behaviour detection, suspect tracking, mobile information and incident management, cybersecurity and more, to further empower your solution.

#### PERFORMANCE MONITORING

Manage and track video assets for one or more sites and receive actionable information about the video network infrastructure. Continuous diagnostics including alerts, advisories, and daily status reports of server, storage, switches, camera and infrastructure disruptions help prevent issues and ensure maximum uptime.

#### **QUICK TO INSTALL**

The EnterpriseServer can be installed in just a few minutes as all the integration work and testing has already been done. It just needs to be plugged in and configured to your project needs.

- High performance with onboard software analytics
- Fully scalable and supports a large number of HD cameras
- Designed to record to external storage as part of larger surveillance infrastructure solutions
- Award-winning technologies

#### Simply Smarter

The EnterpriseServer SE422 is a video-optimised application server, designed to interface with video-optimised, shared external storage such as the Intransa EnterpriseStorage ST350, to eliminate the need for commodity IT servers and storage.

#### Tested & Certified

The Intransa Technology Labs continually test and certify cameras, VMS systems, NVRs and other applications for use with Intransa products for physical security's real-world demanding requirements. This allows for risk-free integration, without the complications of products that are not designed for physical security.

#### Faster & More Powerful

The SE422 combines the high performance Intel® Skylake Xeon® E3-1230v6 quad-core server class processor with up to 3.9 GHz clock speed and fast 2400 MHz DDR4 memory. Its high bandwidth connectivity and unmatched LAN connectivity with 4 GbE ports, gives it the speed and responsiveness for the unique performance requirements of video surveillance infrastructure.

#### Fully Protected

We provide advanced RAID technologies which eliminate disk drive failure - the number one cause of lost video and downtime. Disk drives are hot swappable without interruption in service or loss of data. The second most common failure is power supplies. The SE422 eliminates this by providing dual redundant power supplies. The SE422 only uses ECC RAM and video being stored and transferred within the system is protected.

#### Flexible & Scalable

Choose from a server with two SSD drives for the OS in RAID 1 conguration and options of up to 4 SSD drives with a capacity ranging from 120GB to 6TB. Expand the SE422 with the ST350, allowing capacity to grow by an additional 480TB. This is a perfect conguration for a VMS live database. The SE422 delivers simple, reliable performance to suit all your VMS application needs including recording, failover, archiver, directory and database servers.



Simple. **Powerful and Optimised for video** 

## Contact Info

#### Intransa Systems Inc.

**US Toll Free**: (855) 546 8726

(855) 5INTRANSA

US Tel: +1 (650) 713 2065 +971 4 330 0433 UAE Tel:

General Information: info@intransa.com

Sales: sales@intransa.com Support: support@intransa.com Website: www.intransa.com

Copyright © 2017 Intransa Systems Inc. Specifications are subject to change without notice. Intransa and the Intransa logo are trademarks of Intransa Systems Inc.

VideoAppliance is a trademark of Intransa Systems Inc.

All other names, brands, products, or services are trademarks or registered trademarks of their respective owners.

### Specifications

Core Technology

**CPU Type** Socket Core Logic

Benchmark/Clock speed

Memory size Memory type

Video Storage Performance

Expansion

**Expansion Slot** 

Slot Type

Storage **HDD Bays** Drive support

RAID

Networking

Management

Video

Graphic

On Board I/O

Management Solution

Compliance

Safety

**EMI** 

Physical Characteristics

Server dimensions (in./mm)

Server weight Shipping weight Box dimensions

Power Voltage

Watts

Operating Environment

Operation temperature Non-operation temperature

Humidity Operating altitude Intel Skylake Xeon® E3-1230v6 3.5-3.9GHz

LGA1151

Intel® C236 Chipset 11081/3.5GHz

8GB (expandable to 128GB)

DDR4 2400 ECC Up to 320Mbs / 40MBs

1xPCI-E x16 (Gen3) (Full-Height/HL)

2 x 2.5" and 4 x hot swap 2.5" 120GB to 2TB SSD SATAIII

0, 1, 10, 5

4 x GbE (Intel® i210)

1 x GbE (Intel® i210)

Aspeed AST2300 4 x USB 3.0 ports

USB 3.0 port, (front x2, rear x2)

VGA port (1x rear) 1 x Serial Port (rear)

Remote IPMI support

US/Canada (UL1950-CSA950)

Europe (CE, EN55022 compliance to

EU Directive 89/366/EEC)

Europe (TUV)

US (FCC, CFR47 Part 15, Class A)

Europe (CE, EN55022 class A & EN55024)

24" x 19" x 1.75" / 625 x 482.6 x 44.4 mm

29.6lbs / 13.4kg 36.2lbs / 16.4kg

32.5" x 23.5" x 6" / 825.5 x 597 x 152 mm

Dual redundant 1+1 (Optional)

110/220V AC

750W 80 PLUS Platinum

Designed for 24x7x365 Operation

10°C to 35°C -40°C to 70°C

20% to 90% (non-condensing) 0 to 10,000ft / 0 to 3000m



